

Meet the Xerox<sup>®</sup> PrimeLink C9065/C9070. Engineered to make a great first impression, these intuitive printers come complete with spot-on colour fidelity, best-in-class media latitude and professional finishing capabilities.

SYSTEM SPECIFICATIONS	PRIMELINK C9065		PRIMELINK C9070	
SIMPLEX SPEEDS	COLOUR	BLACK-AND-WHITE	COLOUR	BLACK-AND-WHITE
<b>A4</b> 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 65 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm	Up to 70 ppm Up to 70 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm	Up to 70 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm	Up to 75 ppm Up to 75 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm
<b>A3</b> 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 32 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm Up to 14 ppm Up to 14 ppm	Up to 35 ppm Up to 35 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm	Up to 35 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm Up to 17 ppm	Up to 37 ppm Up to 37 ppm Up to 25 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm
<b>SRA3</b> 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 29 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm Up to 12 ppm	Up to 30 ppm Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm	Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm Up to 12 ppm	Up to 33 ppm Up to 33 ppm Up to 19 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm
AUTO DUPLEX SPEEDS	COLOUR	BLACK-AND-WHITE	COLOUR	BLACK-AND-WHITE
<b>A4</b> Example: 60 to 105 gsm uncoated	Up to 65 ipm 2-sided 32 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 75 ipm 2-sided 37 sheets per minute
A3 Example: 60 to 105 gsm uncoated	Up to 33 ipm 2-sided 16 sheets per minute	Up to 35 ipm 2-sided 17 sheets per minute	Up to 35 ipm 2-sided 17 sheets per minute	Up to 37 ipm 2-sided 18 sheets per minute
Monthly Duty Cycle	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis). <sup>1</sup>			
Average Monthly Print Volume (AMPV)	10,000 to 50,000 pages pe	r month <sup>2</sup>		

Technology	Xerox® EA-Eco toner with Ultra Low Melt Technology (2400 x 2400 dots per inch)		
Control Panel Languages	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan		
ACCESSORIES			
Optional	Xerox <sup>®</sup> EX-C 9065/C9070 Print Server Powered by Fiery <sup>®</sup> Xerox <sup>®</sup> EX 10065/C9070 Print Server Powered by Fiery <sup>®</sup> Xerox <sup>®</sup> EX 0065/C9070 Print Server Powered by Fiery <sup>®</sup> Simple Catch Tray (Europe only) Offset Catch Tray (Europe only) Tray Oversized High Capacity Feeder with Storage Cabinet 2-Tray Oversized High Capacity Feeder a Vertical Transport Kit) Xerox <sup>®</sup> Business Ready Finisher (requires a Vertical Transport Kit) Xerox <sup>®</sup> Business Ready Finisher (requires a Vertical Transport Kit) Xerox <sup>®</sup> Production Ready Finisher (requires a Vertical Transport Kit) Xerox <sup>®</sup> Production Ready Finisher (requires a Vertical Transport Kit) Xerox <sup>®</sup> Production Ready Finisher (requires a Vertical Transport Kit) Xerox <sup>®</sup> Production Ready Finisher (requires Interface Decurler Module) Xerox <sup>®</sup> Production Ready Finisher Plus (includes PFIM Partner Finishing Interface Module) Xerox <sup>®</sup> Production Ready Finisher Plus (includes PFIM Partner Finishing Interface Module; requires Interface Decurler Module) XLS Extension Tray Kits Plockmatic Pro50/35 <sup>™</sup> Booklet Maker Xerox <sup>®</sup> 6/Z Folder Xerox <sup>®</sup> Croso: Purch OHCF Chute MSI Assembly Kit Swedish 4-Hole Punch Envelope Fuser Kit Simple Offset Catch Tray Banner Feed Extension Long USB HUB Kit GBC <sup>®</sup> AdvancedPunch <sup>™</sup> Pro Xerox <sup>®</sup> SquareFold <sup>®</sup> Trimmer Module Xerox <sup>®</sup> Inserter Convenience Stapler Foreign Device Interface Kit Mobility Plate PostScript Kit VOIP Fax (Stt) Kit Xerox <sup>®</sup> Workplace Suite, Xerox <sup>®</sup> Workplace Cloud For More information on Xerox <sup>®</sup> Apps and Solutions, visit <b>www.xerox.com/AppGallery</b> .		
ELECTRICAL REQUIREMEN			
Europe	Voltage: 220-240V Frequency: 50/60 Hz +/- 3 %, 10 A		
Accessories Europe:	Each module requires 220V, 10 A		
POWER CONSUMPTION			
Running (Average)	PrimeLink C9065: 1,052 watts; PrimeLink C9070: 1,250 watts		
Sleep Mode (Average)	3 watts (Default time to Sleep mode = 1 min.)		
Low Power Mode Recovery Time	Less than 20 seconds		

OPERATING ENVIRONME	NT		
Required Temperature Range	10° to 28° C (Relative Humidity less than 62.5% when temp is 32° C or less)		
Required Relative Humidity	15% to 85% (no condensation)		
Sound Power Levels	Operating: 6.8 B(A); Standby: 3.6	5 B(A)	
Sound Pressure Levels	Operating: 56 dB(A); Standby: 1	8 dB(A)	
Weight (approximate base unit only)	273 kg		
DIMENSIONS	WIDTH	DEPTH	HEIGHT
Base Unit w/ Offset Catch Tray	1,574 mm	803.5 mm	1,391.5 mm
Base Unit w/ Business Ready Finisher	2,009 mm	803.5 mm	1,391.5 mm
Base Unit w/ Business Ready Booklet Maker Finisher	2,068 mm	803.5 mm	1,391.5 mm
Base Unit w/ Business Ready Booklet Maker Finisher and C Fold / Z Fold Unit	2,301 mm	803.5 mm	1,391.5 mm
Base Unit w/ Production Ready Finisher	2,120.63 mm	803.5 mm	1,391.5 mm
Base Unit w/ Production Ready Booklet Maker Finisher	2,399.43 mm	803.5 mm	1,391.5 mm
Xerox <sup>®</sup> Crease/ Two-sided Trimmer	760.5 mm	714.3 mm	991.5 mm
Interface Decurler Module	340 mm	724.3 mm	991.5 mm
Xerox <sup>®</sup> SquareFold <sup>®</sup> Trimmer	1,066.3 mm	724 mm	558.8 mm
High Capacity Feeder	389 mm	614 mm	377 mm
One Tray Oversized High Capacity Feeder	988 mm	762 mm	992 mm
Two Tray Oversized High Capacity Feeder	988 mm	762 mm	992 mm
CERTIFICATIONS	To view the latest list of certifica	tions, go to <b>www.xerox.com/C</b>	OfficeCertifications.
Graphic Arts Credentials	FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™ (certified IDEAlliance Digital Press Certified *requires an additional Print Serv	ed to GRACoL <sup>®</sup> specifications	

PAPER HANDLING		
SINGLE-PASS DUPLEX AU	TOMATIC DOCUMENT FEEDER (DADF) - NETWORK SCANNING	
Capacity <sup>3</sup>	250 sheets of plain paper – 75 gsm	
Speed	Up to 270 ipm colour / 270 ipm black-and-white (2-sided, A4)	
Paper Sizes	Custom sizes: A5 to A3	
Weights	38 to 200 gsm	
TRAY 5 (BYPASS)		
Capacity <sup>3</sup>	Up to 250 sheets	
Sizes	Custom sizes: 100 x 148 mm to 330.2 x 482.6 mm (A5 to SRA3); XLS sheet size: 330 x 660 mm	
Weights	60 to 350 gsm (60 to 350 gsm uncoated; 106 to 350 gsm coated); XLS sheet: 60-220 gsm	
Envelope Capacity	30 to 50 envelopes	
Envelope Sizes	#10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5 (Bypass). Paper Size Default within tools. Run flap open at the trail edge.) Custom sizes: 190 x 170 mm to 240 x 173 mm. Digital Laser envelopes recommended.	
Envelope Weights	75 to 90 gsm	
TRAYS 1 TO 4		
Capacity <sup>3</sup>	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets	
Sizes	Tray 1: A5 to SRA3 Tray 2: A5 to A3 Tray 3: B5, A4 Tray 4: B5, A4	
Weights	Trays 1 and 2: 60 to 256 gsm (60 to 256 gsm uncoated; 106 to 220 gsm coated) Trays 3 and 4: 60 to 256 gsm (60 to 256 gsm uncoated; 106 to 220 gsm coated)	
OPTIONAL HIGH CAPACIT	Y FEEDER (HCF)	
Capacity <sup>3</sup>	2,000 sheets	
Sizes	184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)	
Weights	64 to 220 gsm (uncoated and coated)	
OPTIONAL OVERSIZED HI	GH CAPACITY FEEDER (OHCF) – 1 OR 2 TRAY OPTIONS	
Capacity <sup>3</sup>	1 Tray OHCF: 2,000 sheets plus Storage Cabinet 2 Tray OHCF: 4,000 sheets	
Sizes	1 Tray OHCF: 182 x 250 mm (B5) to 330x660 mm 2 Tray OHCF: 102 x 152 mm to 330x660 mm	
Weights	60 to 350 gsm (uncoated and coated); XLS sheet: 60-220 gsm	
TOTAL CAPACITY		
Standard Capacity	3,250 sheets (includes Tray 5 (Bypass) and Trays 1-4)	
Maximum Capacity	7,250 sheets (includes Tray 5 (Bypass), Trays 1-4 and Two-tray Oversized High Capacity Feeder)	
Automatic Two-Sided	256 gsm auto duplex 350 gsm manual duplex for all stocks from Tray 5 (Bypass) and optional Oversized High Capacity Feeder	

FINISHING		
OFFSET CATCH TRAY		
Capacity <sup>3</sup>	Up to 500-sheet stacking	
Simple Catch Tray (Europe Only)	Up to 500-sheet stacking	
OPTIONAL BUSINESS	READY FINISHER	
Capacity <sup>3</sup>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple), A3 or 200 sets (single-position staple) A4	
Sizes	A6 to SRA3 for stacking B5 to A3 for stapling A5 output to top tray; punch and offset	
Weights	60 to 350gsm (coated and uncoated) Top Tray 60 to 256 gsm (coated and uncoated) Stacker Tray	
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported	
Hole Punch	2-4 Hole Punch 4 Hole Swedish Punch (Optional)	
OPTIONAL BUSINESS	READY BOOKLET MAKER FINISHER	
Capacity <sup>3</sup>	Offsetting Top Tray: 500 sheets of A4 unstapled Stacking Stapling Tray: 1,500 sheets of A4 / A3 / SRA3 unstapled or 200 stapled sets of A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of A3 / SRA3	
Sizes	A6 to SRA3 for stacking B5 to A3 for stapling A5 output to top tray; punch and offset	
Weights	60 to 350 gsm (coated and uncoated) Top Tray 60 to 256 gsm (coated and uncoated) Stacker Tray 60 to 256 gsm (coated and uncoated) Booklet Maker	
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported	
Hole Punch	2-4 Hole Punch 4 Hole Swedish Punch (Optional)	
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated), Bi- fold up to 5 sheets A3, A4, SRA3 supported	
OPTIONAL XEROX® C/2	Z FOLDER	
Types	C Fold, Z Fold and Z Half Fold	
Capacity <sup>3</sup>	40 sheets	
Sizes	C Fold and Z Fold: Letter – A4 SEF only Z Half Fold: A3 only	
Weights	64 to 90 gsm	
Output Tray	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold	
OPTIONAL PRODUCTIO	ON READY FINISHER (REQUIRES INTERFACE DECURLER MODULE)	
Capacity	Top Tray: 500 sheets of 80 gsm, A4 Lower Tray: 3,000 sheets of 80 gsm, A4	
Sizes	A6 to SRA3	
Weights	60 to 350 gsm (coated and uncoated) Top Tray 60 to 256 gsm (coated and uncoated) Stacker Tray	

Multiposition Stapling	Up to 100 sheets of 80 gsm	
Hole-punching	2-4 Hole Punch 4 Hole Swedish Punch (Optional)	
<b>Inserting Capacity</b> Capacity: Sizes: Weights:	250 sheets of 350 gsm A3, A4, B4, B5 64 to 350 gsm	
Decurling	Included with Interface Decurler Module and Standard Finisher Bidirectional with Auto and Manual settings	
OPTIONAL PRODUCTION	READY FINISHER PLUS (REQUIRES INTERFACE DECURLER MODULE)	
	Provides same function as the Production Ready Finisher with a 500-sheet top tray and 2,000-sheet stacker tray. Used to connect third-party inline finishing options. Includes PFIM Partner Finishing Interface Module.	
OPTIONAL PRODUCTION	READY FINISHER WITH BOOKLET MAKER (REQUIRES INTERFACE DECURLER MODULE)	
Capacity	Top Tray: 500 sheets of 80 gsm, / A4 Lower Tray: 2,000 sheets of 80 gsm, / A4	
Sizes	A6 to SRA3	
Weights	60 to 350 gsm (coated and uncoated) Top Tray 60 to 256 gsm (coated and uncoated) Stacker Tray 60 to 256 gsm (coated and uncoated) Booklet Maker	
Multi-position Stapling	Up to 100 sheets of 80 gsm	
Hole-punching	2-4 Hole Punch (Optional) 4 Hole Swedish Punch (Optional)	
<b>Inserting Capacity</b> Capacity: Sizes: Weights:	250 sheets of 350 gsm A3, A4, B4, B5 64 to 350 gsm	
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings	
Booklet Making Capacity	Saddle-stitch 2 to 30 sheets of 79 gsm (uncoated) or 2 to 25 sheets (coated); Bi-fold up to 5 sheets A4, B4, A3, SRA3	
OPTIONAL XEROX® CREAS	E AND TWO-SIDED TRIMMER	
Trim Sheet Sizes	194 mm x 210 mm to 330.2 mm x 488 mm	
Trim Booklet Sizes	182 mm x 257 mm to 330.2 mm x 488 mm	
Crease Weights	106-350 gsm coated	
Weights	60-350 gsm (uncoated) and 106-350 gsm (coated)	
OPTIONAL GBC <sup>®</sup> ADVANC	EDPUNCH PRO	
Punch Configuration Sizes	148 x 210 mm (A5) LEF to 330 x 488 mm (SRA3) SEF	
Weights	75 to 300 gsm (uncoated); 106 to 300 gsm (coated)	
Dies	Wide selection of slide-in / slide-out GBC punch die sets available	
OPTIONAL XEROX <sup>®</sup> SQUA	REFOLD <sup>®</sup> TRIMMER MODULE	
Capacity	5 to 20-sheet booklets (up to 80 imaged sides) at 90 gsm 5 to 25-sheet booklets (up to 100 imaged sides) at 80 gsm	
Sizes	Custom sizes: A4 to SRA3	
Weights	64 to 350 gsm	

OPTIONAL CONVENIENCE	E STAPLER	
Capacity	50 sheets (90 gsm media)	
PRINT		
Print Resolution	Up to 2400 x 2400 dpi	
Line Screens	600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected)	
Registration	<ul> <li>Advanced registration technology for tighter control</li> <li>Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (Available on all configurations as a Maintenance Tool: Alignment Adjustsment)</li> <li>+/-1.2 mm front to back registration Internal Trays</li> </ul>	
First-Print-Out Time	PS- A4 LEF Simplex Colour 10.4 seconds / Black-and-white 8.5 seconds	
Print Feαtures	<ul> <li>Print, copy, fax and scan, including scan to PC, USB or email, and mobile printing</li> <li>Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt EA-Eco toner for a smooth finish</li> <li>Makes mobile printing simpler and more convenient</li> <li>Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 350 gsm</li> <li>Xerox Extensible Interface Platform<sup>®</sup> (EIP 3.7.3) allows you to connect to third-party software solutions that you can access from the touch-screen of the device or on your own mobile device.</li> <li>Your choice of servers to best fit your environment: <ul> <li>Xerox<sup>®</sup> EX-c PrimeLink C9065/C9070 Print Server Powered by Fiery<sup>®</sup></li> <li>Xerox<sup>®</sup> EX PrimeLink C9065/C9070 Print Server Powered by Fiery</li> <li>Xerox<sup>®</sup> EX PrimeLink C9065/C9070 Print Server Powered by Fiery</li> </ul> </li> <li>Inline finishing options offer a professional polish with banner printing, stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters.</li> <li>Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support.</li> </ul>	
Print Drivers	Xerox <sup>®</sup> Smart Start Driver Installer, Xerox <sup>®</sup> Global Print Driver <sup>®</sup> (v3, v4)	
PRINT SOLUTIONS		
Mobile Printing (optional)	Apple <sup>®</sup> AirPrint <sup>®</sup> , Google Cloud Print <sup>™</sup> Ready, Mopria <sup>®</sup> Print Service Plug-in for Android, Wi-Fi Direct Printing, Xerox <sup>®</sup> @PrintByXerox App, See more at <b>www.xerox.com/MobileSolutions</b> ; Xerox <sup>®</sup> Workplace Cloud/Suite Mobile Print Solution. Learn more at <b>www.xerox.com/MobilePrintApp</b> .	
Xerox Apps	On Box Apps include Xerox <sup>®</sup> @printbyXerox App for mobile printing and Xerox App Gallery to download a multitude of Print Management Apps.	
СОРҮ		
First-Copy-Out Time From the Platen: From the DADF:	As fast as 7.8 seconds colour / 5.1 seconds black-and-white As fast as 9.6 seconds colour / 5.3 seconds black-and-white	
Warm Up Time	90 seconds (from cold powered down to Ready Copy)	
Digital Imaging	Auto colour Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) Includes subtypes lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, colour shift and saturation	

Reduce / Enlarge	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages	
Special Features		
SCAN		
Concurrency	Scan while printing or while it is transferring scan to network or fax jobs	
Scan Features	Mixed size originals Edge erase Reduction/enlargement Fit to size Scan build job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto background and shadow suppression Job flow sheets Scan to USB Preview scan job	
INPUT SPEED	Up to 270 images per minute Duplex	
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi	
Maximum Scan Area	Originals up to A3	
Network Print Services	Port 9100 RFC 1179 (LPR) Print to Mailbox and Release	

File Formats	PDF Image Only PDF Searchable PDF (Linearized) PDF (A-1 Level A) TIFF V6 JFIF XPS	
Document Management Fields (Metadata)	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard	
Scan Features	Scan to Home Scan to Desktop WIA Scan to Desktop TWAIN Scan to Mailbox Scan to FTP Scan to FTP (via EIP solution) Scan via SMB Scan via HTTP Scan via HTTPS Scan to USB Storage Device Scan to USB Storage Device Scan to Fax Server Scan to Multiple Destinations Scan to Microsoft Network Folder	
Supported Scan Destinations (Standard)	Scan to Email, Scan to Folder, to PC, to Mailbox (private and public), Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview	
Scan to Email Features	Colour scanning, Auto Colour, Greyscale, Black-and-white Direct document email from device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job	
Authentication	SMTP authentication, POP before SMTP, System credentials Single sign-on (LDAP, SMB, Kerberos authentication) Scanning Security-TLS	
FAX (OPTIONAL) – ONE OF	THREE LINE FAX OPTIONS	
Maximum Scan Area	210 mm x 297 mm (A3)	
Fax Send Features	iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination	
Fax Print Features	Print from USB Storage Device Media Print Unicode Printing	
Fax Features	iFax Lan Fax IP Fax (optional) Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination	

DEVICE MANAGEMENT		
XEROX <sup>®</sup> CENTREWARE <sup>®</sup> INT	ERNET SERVICES – INTEGRATED WEB PAGES PROVIDED BY THE DEVICE	
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts	
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Internet Explorer Safari Mozilla Firefox Opera Chrome	
Support	Install print/scan drivers and online support available via web page	
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese	
REMOTE SERVICES		
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox <sup>®</sup> device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
SECURITY		
Features	Access Controls AES 256-bit Encryption Audit Log Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Programme Falsification (XCP Plug-in) Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite IP Address Filtering IPsec Network Authentication Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management SNMPv3 Status Protocol (OCSP) TLS/SSL (TLS 1.0, 1.1, 1.2)	
PRINT SERVER		
XEROX <sup>®</sup> INTEGRATED COL		
Processor	1.6 GHz Dual-core	
Memory	4 GB system plus 1 GB page memory	
System Disk	320 GB Hard Disk Drive	
Display	264.2 mm colour touchscreen flat-panel	
Device Operating System	Linux	

PDLs Page Description Languages	Adobe <sup>®</sup> PostScript <sup>®</sup> 3 <sup>™</sup> PDF PCL <sup>®</sup> 5c, 6 XML Paper Specification (XPS <sup>®</sup> ) (optional)	
Operating Systems	Windows <sup>®</sup> XP Windows Server 2003 (32- and 64-bit) Windows Server 2008 (32- and 64-bit) Windows Server 2012 Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Mac OS <sup>®</sup> 10.7 and above	Solaris® 9, 10 HP-UX® 11 v2 IBM® AIX® 5 Red Hat® Fecora® Core 15-17 Red Hat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® Unix®
Print Drivers Supported	is also added for the Xerox <sup>®</sup> PrimeLink C9065/(	ecifics. As new operating system versions are added, support 9070 Printer. Also note that there is more than one print g., digital front ends, Xerox® Global Print Driver) 008 R2, 64-bit; Windows Server 2012 64-bit;

Feαtures	Automatic two-sided Bi-directional print drivers provide device and job status Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) Secure print Delay print Embedded web server for remote control/monitor/setup Enhanced gloss Sample set Booklet creation Cover selection Paper selection by attribute N-up Watermarks Banner sheets Banner printing Fit to new paper size Output tray selection Print calibration (with EFI) Print from USB (No Print Driver required)	
Connectivity	Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec)	
ADDITIONAL PRINT SERV	ER OPTIONS	
XEROX <sup>®</sup> EX-C C9065/C9070	O PRINT SERVER POWERED BY FIERY®	
Processor	AMD <sup>®</sup> GX-424CC processor 2.4 GHz	
Memory	2 GB RAM	
Hard Drive	500 GB	
Server Operating System	Linux®	
Print Languages (PDL)	Adobe PostScript <sup>®</sup> Level 1,2,3, Adobe PDF, EPS, PCL <sup>®</sup> 6C, TIFF, JPG, and MicroSoft <sup>®</sup> native formats via Fiery <sup>®</sup> Hot Folders	
Features	<ul> <li>Easy-to-use colour adjustment tools that deliver outstanding colour quality from all applications and file formats.</li> <li>Print logo and corporate colours correctly (including PANTONE colours)</li> <li>Print high-quality photos and images</li> <li>Use Fiery VUE, the "visual print driver," to create and print professional booklets quickly, easily and cost effectively in-house</li> <li>Easily print files with mixed paper sizes and types</li> <li>Fully integrated with Xerox<sup>®</sup> ConnectKey<sup>®</sup> Apps</li> <li>Paper Catalogue</li> <li>Command WorkStation</li> <li>Fiery Freeform</li> <li>Fiery Remote Scan</li> </ul>	
Connectivity	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100	
Additional Options	<ul> <li>Options Bundle <ul> <li>Fiery Spot-On<sup>™</sup> with PANTONE approved libraries</li> <li>Fiery Hot Folders</li> <li>Fiery Virtual Printers</li> <li>Auto Trapping</li> </ul> </li> <li>Colour Profiler Suite (with ES2000)</li> <li>Network Hub Kit</li> <li>Spot On</li> <li>Hot Folders/ Virtual Printers</li> </ul>	
XEROX <sup>®</sup> EX-I C9065/C9070	PRINT SERVER POWERED BY FIERY®	
Processor	Intel 3-6100 (3.7 GHz) Processor (Performance optimised by proprietary combination of EFI Technology, VX600 ASIC and software)	
Memory	4 GB	

Hard Drive	500 GB		
Server Operating System	Linux®		
Print Languages (PDL)	Adobe PostScript <sup>®</sup> Level 1,2,3, Adobe PDF, EPS, PCL <sup>®</sup> 6C, TIFF, JPG, and MicroSoft <sup>®</sup> native formats via Fiery <sup>®</sup> Hot Folders		
Feαtures	<ul> <li>Productivity starts with a fast RIP. The Integrated Fiery Colour Server enables you to print large and/or complex Microsoft<sup>®</sup> Office<sup>®</sup> documents, PowerPoint<sup>®</sup> files and colour-critical PDFs accurately and quickly.</li> <li>Fully integrated with Xerox<sup>®</sup> ConnectKey<sup>®</sup> Apps.</li> <li>Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers.</li> <li>Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the pre-set drivers configured for the task.</li> <li>Get the colour right. Produce precise, exact colour from all applications, platforms and formats with Fiery colour management tools.</li> <li>Turn up the impact with variable information. Customise your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Colour Server's basic variable data printing capabilitie</li> <li>Print high-quality photos and images</li> <li>Use Fiery VUE, the "visual print driver," to create and print professional booklets quickly, easily and cost effectively in-house</li> <li>Easily print files with mixed paper sizes and types</li> <li>Command WorkStation</li> <li>Fiery JDF</li> <li>Secure Erase</li> <li>Paper Catalogue</li> <li>Fiery Compose</li> <li>Fiery Remote Scan</li> </ul>		
Connectivity	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100		
Additional Options	<ul> <li>Productivity Package <ul> <li>Fiery ImageViewer</li> <li>Fiery Image Enhance Visual Editor</li> <li>Control Bar Builder</li> <li>Postflight Report</li> <li>Configurable Auto Trapping</li> <li>Paper Simulation</li> <li>Graphic Arts Filters for Hot Folders</li> <li>Rush Print, Schedule Print and Print/Process Next</li> <li>Fiery JobFlow Base</li> <li>Fiery impose</li> <li>Colour Profiler Suite (with ES2000)</li> <li>Network Hub Kit</li> </ul></li></ul>		
	For more information, go to <b>www.xerox.com</b>		
XEROX <sup>®</sup> EX C9065/C9070 I	PRINT SERVER POWERED BY FIERY®		
Processor	Intel <sup>®</sup> Core™ i5-6500 Processor (3.2 up to 3.6 GHz with Turbo), Quad Core		
Memory	8 GB		
Hard Drive	1 TB		
Server Operating System	Windows 10		
Print Languages (PDL)	Adobe PostScript® Level 3, Adobe PDF, EPS, PCL® 6C, PCL 5, TIFF, JPG, MicroSoft® native formats via Fiery® Hot Folders and Adobe PDF Print Engine (APPE)		
Features	<ul> <li>Job-based Calibration Integration <ul> <li>Fiery Spot-On finds the best match of PANTONE<sup>®</sup>, PANTONE Series, RGB, CMYK, L*a*b* and Spot Colours</li> <li>Colour Modes for professional proofing and enhanced production colour requirements – Maximum print density</li> <li>Fully integrated with Xerox ConnectKey<sup>®</sup> Apps.</li> <li>Fiery technology increases your profits by delivering high-impact documents with vibrant images and colour that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production.</li> </ul> </li> </ul>		

	<ul> <li>The Fiery Command WorkStation increases your production and reduces errors and waste by centralising job management via its intuitive user interface. Simplify your labour-intensive document composition and imposition tasks even more by using Fiery SeeQuence Impose and Compose's intuitive interface.</li> <li>Print high-quality photos and images</li> <li>Use Fiery VUE, the "visual print driver," to create and print professional booklets quickly, easily and cost effectively in-house</li> <li>Easily print files with mixed paper sizes and types</li> <li>Paper Catalogue</li> <li>Sequential Printing</li> <li>Fiery JDF</li> <li>Insert Tabs</li> </ul>			
Connectivity	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100			
Additional Options For more information, go to <b>www.xerox.com</b>	<ul> <li>Fiery Graphic Arts Package, Premium Edition (optional) provides expert tools for preflighting and troubleshooting jobs</li> <li>Fiery Colour Profiler Suite (optional) creates, verifies and edits colour profiles with a single profiling solution</li> <li>Furniture Kit – Monitor, Keyboard, and Mouse</li> <li>Colour Profiler Suite (with ES2000)</li> <li>Removable HDD</li> <li>Network Hub Kit</li> </ul>			
SUPPLIES		YIELD	PART NUMBER	
<b>Toner Cartridges</b> (Metered)	Black	30,000 pages <sup>4</sup>	006R01521	
	Cyan	34,000 pages <sup>4</sup>	006R01524	
	Magenta	32,000 pages <sup>4</sup>	006R01523	
	Yellow	34,000 pages <sup>4</sup>	006R01522	
Toner Cartridges (Sold)	Black	30,000 pages <sup>4</sup>	006R01734 (NASG,ESG) 006R01738 (DMO)	
	Cyan	34,000 pages <sup>4</sup>	006R01737 (NASG, ESG) 006R01741 (DMO)	
	Magenta	32,000 pages <sup>4</sup>	006R01736 (NASG, ESG) 006R01740 (DMO)	
	Yellow	34,000 pages <sup>4</sup>	006R01735 (NASG, ESG) 006R01739 (DMO)	
Black Drum Cartridge	1 Cartridge	190,000 pages <sup>4</sup>	013R00663	
Colour Drum Cartridge	1 Cartridge per Colour	85,000 pages <sup>4</sup>	013R00664	
Charge Corotron	For Black Drum	190,000 pages <sup>4</sup>	013R00650	
Fuser	110V 220V	200,000 pages <sup>4</sup> 200,000 pages <sup>4</sup>	008R13102 008R13065	
Waste Toner Container	1 Cartridge	50,000 pages <sup>4</sup>	008R12990	
Feed Roll Kits	1 Assembly	300,000 pages <sup>4</sup>	008R13169	

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

Approximate pages. Declared Yield based on 5 page job size, 30% colour and 70% black-and-white ratio, using A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/About-Xerox/Recycling.

#### Learn more at www.xerox.com/PrimeLink

©2019 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, ConnectKey®, Global Print Driver®, PrimeLink®, SquareFold® and Xerox Extensible Interface Platform® and are trademarks of Xerox Corporation in the United States and/or other countries. EFI, Splash, Fiery® and RPX-iii are trademarks of Electronics for Imaging, Inc. Product appearance, build status and/or specifications are subject to change without notice. 9/19 PN03335\_T91 BR27331 PC9SS-01EA

