

## **Transfer press PT-15**

## **Product Information**

The **PT-15** is a high quality technologically advanced low cost manual press, ideal for most users. The swing head operation gives a perfect view of the transfer and garment allowing accurate and easy application, along with safety of operation.

Fitted with our unique advanced computerised controller to accurately monitor both temperature and time.

Pressure adjustment is by a fingertip control knob making this machine ideal for light, medium and heavy pressure requirements.

The **PT-15** is a manually operated heat press for transfer printing and material fusing.

The work area of the **PT-15** is  $38 \times 50$  cm ( $15 \times 20''$ ) but machines may have, to special order, 5 optional smaller sized interchangeable worktables of different sizes and various shapes:

15.3 x 15.3 cm (6 x 6") 20.5 x 20.5 cm (8 x 8") 25.4 x 25.4 cm (10 x 10") 30.5 x 30.5 cm (12 x 12") 38.0 x 38.0 cm (15 x 15")

The PT-15 bears the CE Marking.



## **Technical Data**

**Power Consumption Power Supply** Working temperature **Display Timer Range** Machine height open Machine height closed Machine width Machine width loading Machine depth Machine depth loading Work area required Weight export packed Size export packed Net weight Press pad dimensions Fuses A-weighted noise level

## **European Version**

2500 Watts 230 Volts AC 70-230°C 0 - 10 min 65 cm 35 cm 51 cm 94 cm 89 cm 120 cm 110 x 92 x 64 cm 52 kg 91 (L) x 62 (B) x 42 (H) cm 45 kg 38 x 50 cm 11 A < 70 dB(A)

28/07/2011

POLI-TAPE Klebefolien GmbH Zeppelinstraße 17 53424 Remagen – GERMANY

Phone:	+49	(0)	2642	_	9836	0
Fax:	+49	(0)	2642	-	9836	37

E-Mail: info@poli-tape.de Internet: www.poli-tape.de The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.